
## FORD TRUCKS 3542P EURO6





Basic Features			
Vehicle Type	Concrete Pump		
Axle	6x4		
Emission	Euro 6		
Cabin Type	Day Cab		
Wheelbase (mm)	4500		

Liigiile	
Туре	Ecotorq 12,7 liters
Displacement (cc)	12740
Bore x Stroke	130 mm x 160 mm
Power	420 PS (308,9 kW ) / 1800 rpm
Torque	2150 Nm / 1000-1300 rpm
Compression Ratio	17 +/- 0,5 : 1
Oll Filling Malayses	FO.1

 Oil Filling Volume
 50 L

 Coolant Volume
 57 L

 Transmission
 430 mm Single Disc

Manuel Transmission / Ratios (1. gear - 16. gear) ZF 16S 2230 (13,805-0,836)

Steering

Power assisted single circuit

Cnassis				
Chassis Thickness	10 mm with Local Reinforcement			
Chassis Strength	500 MPa			
Suspension (Front / Rear)	90 mm Parabolic Leaf Springs / 100 mm Parabolic Tandem Suspension			
Axle	Hub Reduction			
Axle Ratio	4,08			
Tyres	315/80 R 22,5			
Wheel Rim	22,5 x 9 Steel			

Braking System
Brakes (Ø mm x mm Length)
410 x 200 Z-Cam Brake System

Braking System Dual Brake Circuit - Air Processing Unit with Integrated Oil Seperator and Heater

Engine Brake Power max. 320 kW (Engine Level)

Electrical SystemBattery24V, 2 x 12V 150 AhAlternator / Starter Motor130 A / 6,5 kW

 Tanks

 Fuel Tank
 315 L Steel

 SCR Tank
 55 L



Dimensions (mm)	
Front Overhang	1500
Wheelbase	4500
Overall Length	9090
Distance Between 2 <sup>nd</sup> and 3 <sup>th</sup> Wheel Centers	1350
Overall Cab Length	1820
Overall Vehicle Height	3152
Overall Vehicle Width (Excluding Mirrors)	2540
Chassis Width	770
Rear Overhang	1740
Useful Chassis Length	6687
Chassis Height-Front	1116
Chassis Height-Rear	1147
Ground Clearance-Front	382
Ground Clearance-Rear	294
Turning Radius	9790

Weights (kg)	1. Axle	2. Axle	3. Axle	Total
Technically Permissible Weights	8000	13400	13400	34000
Kerb Weight	5525	2217	2217	9959
Payload	2475	11183	11183	24041
GVM (Legal)	8000	9500	9500	26000

## STANDARD EQUIPMENT

- Manual Air Conditioner
- AM/FM/Aux In/USB/Bluetooth (Radio with Bluetooth)
- Conventional 4-point independent Cab Suspension for Day Cabin
- Cruise Control
- Drum Brake
- Engine Brake
- Anti-Lock Brake System (ABS)
- Pad Wear Indicator
- Differential Lock
- Electrically Operated Windows
- Electrically Operated and Heated Side mirrors
- Electrically Operated Headlight Leveling
- Rake and Reach Adjustable Steering Column
- Heated and Air Suspended Driver Seat and Fixed Passenger Seat
- Lumbar Support
- Front Vehicle Antiroll Bar
- Immobilizer
- Single Key with Remote Control and Central Locking
- Home Safe Lights
- Approach Lights
- Double Roof Marker Lamps
- Spare Wheel
- Short Bumper
- Switchable Air Compressor for Improved Fuel Economy
- Rear Window
- Horizontal Exhaust
- Tachograph
- Front Towing Hooks (Double Hook)
- Oil Pan Protection

## **OPTIONAL EQUIPMENT**

- Cold Pack (Includes Wet Type Heater and 225 Ah Battery)
- Engine Driven PTO (includes Power Take off Control Unit)
- Manually Operated Sunroof
- Auxiliary Cabin Heater (Wet Type)
- Power Cab Tilting
- Metallic Paint / Special Colors
- Lateral Protection
- Dual Passenger Seat
- Automatic Traction Control (ATC)
- Less Spare Tire